



## Mobile motorized height adjustable stand for Interactive Flatpanel displays up to 86" Product datasheet



### Mobile double-column motorized height adjustable floor stand

The double-column design guarantees the stability needed to work with Interactive Touchscreens up to 84" diagonal with a 265 Lbs.[120 kg] total weight capacity. The wired remote control unit (no batteries) can be placed at a convenient and easy to reach location, allowing the user to adjust the height of the screen safely and quietly. The motorized stand has an anti collision feature to prevent accidental pinching, when the system is moving and senses an obstruction it will stop and retreat. On the backside of the integrated vesa mounting box (max 600x400) a lock-box is located where the electronic controls are safely located, this lock-box can be used to place a mini-PC, thin-client PC or NUC. The 26" travel will guarantee full screen access to all users, and as such the product is also ideal for wheelchair users.

With the optional accessories the product can be equipped for use with teleconferencing equipment, a document camera, a soundbar and a laptop or keyboard tray.

**Contact information:** Sales manager North America: Sjoerd Ory; phone: +1 778 241 4029; email: [s.ory@tregout.com](mailto:s.ory@tregout.com)

Part number	Description
487A01	Mobile motorized height adjustable stand travel 26" black max 265 Lbs.
481A101	Laptop or keyboard support tray bottom mounting
481A102	Adapter set for screens with VESA 800x400 and 800x200
481A103	Adapter set for screens with VESA 800x600
481A104	Conferencing camera support tray top or bottom mounting
481A105	Universal bracket for Soundbar mounting

# Mobile motorized height adjustable stand for Interactive Flatpanel displays up to 86"

Technical specifications	Length	Width	Height	Weight
Product dimensions (without screen)	41.4" [1051]	26.9"[683]	44.5"[1130]	105.6 Lbs [48kg]
Shipping dimensions (boxed)	45,.7"[1160]	31.5"[800]	11.85"[300]	110 Lbs [50kg]
Travel (center of VESA pattern to floor)	26"[660] (min: 35.6" / max: 61.6") ; Speed 1.5"/Sec. [38 mm/Sec.]			
Maximum screen weight (size)	254 Lbs. [115kg] (86" diagonal)			
VESA bracket / screen interface	Included from 200x200 up to 600x400 ; optional 800x400 and 800x600			
Safety / certification	Anti-collision feature; UL certified actuator; UL registered (UR) pending; CE; ISO-EN60950			
Material and color	Steel structural parts, powder coated black textured RAL9005			
Features	Lockbox, keys included; 4" diam. non-marking wheels			
Electric	120V / 60Hz; 200W piezo motor; 10% duty cycle (6min/hour); UL962 cert.			

